

APPENDIX **A**

*Thermophysical Properties of Matter*¹

| <i>Table</i> | <i>Page</i> |
|--|-------------|
| A.1 Thermophysical Properties of Selected Metallic Solids | 899 |
| A.2 Thermophysical Properties of Selected Nonmetallic Solids | 903 |
| A.3 Thermophysical Properties of Common Materials | 905 |
| Structural Building Materials | 905 |
| Insulating Materials and Systems | 906 |
| Industrial Insulation | 907 |
| Other Materials | 909 |
| A.4 Thermophysical Properties of Gases at Atmospheric Pressure | 911 |
| A.5 Thermophysical Properties of Saturated Fluids | 916 |
| Saturated Liquids | 916 |
| Saturated Liquid–Vapor, 1 atm | 918 |
| A.6 Thermophysical Properties of Saturated Water | 919 |
| A.7 Thermophysical Properties of Liquid Metals | 921 |
| A.8 Binary Diffusion Coefficients at One Atmosphere | 922 |
| A.9 Henry’s Constant for Selected Gases in Water at Moderate Pressure | 923 |
| A.10 The Solubility of Selected Gases and Solids | 923 |

¹The convention used to present numerical values of the properties is illustrated by this example:

| T (K) | $\nu \cdot 10^7$ (m ² /s) | $k \cdot 10^3$ (W/m · K) |
|------------|---|-----------------------------|
| 300 | 0.349 | 521 |

where $\nu = 0.349 \times 10^{-7}$ m²/s and $k = 521 \times 10^{-3} = 0.521$ W/m · K at 300 K.

| | | |
|-------------|--|-----|
| A.11 | Total, Normal (n) or Hemispherical (h) Emissivity of Selected Surfaces | 924 |
| | Metallic Solids and Their Oxides | 924 |
| | Nonmetallic Substances | 925 |
| A.12 | Solar Radiative Properties for Selected Materials | 926 |
| | References | 927 |

TABLE A.1 Thermophysical Properties of Selected Metallic Solids^a

| Composition | Melting Point (K) | Properties at 300 K | | | | | Properties at Various Temperatures (K) | | | | | | | | | |
|---|-------------------|-----------------------------|----------------|-------------|---|-------------|--|------|------|------|------|------|------|------|------|------|
| | | ρ (kg/m ³) | c_p (J/kg·K) | k (W/m·K) | $\alpha \cdot 10^6$ (m ² /s) | | 100 | 200 | 400 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 |
| | | | | | | k (W/m·K) | | | | | | | | | | |
| Aluminum Pure | 933 | 2702 | 903 | 237 | 97.1 | 302 | 237 | 240 | 231 | 218 | | | | | | |
| Alloy 2024-T6 (4.5% Cu, 1.5% Mg, 0.6% Mn) | 775 | 2770 | 875 | 177 | 73.0 | 65 | 798 | 186 | 186 | 1146 | | | | | | |
| Alloy 195, Cast (4.5% Cu) | | 2790 | 883 | 168 | 68.2 | 473 | 787 | 925 | 1042 | | | | | | | |
| Beryllium | 1550 | 1850 | 1825 | 200 | 59.2 | 990 | 301 | 161 | 126 | 106 | 90.8 | 78.7 | | | | |
| Bismuth | 545 | 9780 | 122 | 7.86 | 6.59 | 16.5 | 1114 | 2191 | 2604 | 2823 | 3018 | 3227 | 3519 | | | |
| Boron | 2573 | 2500 | 1107 | 27.0 | 9.76 | 190 | 55.5 | 16.8 | 10.6 | 9.60 | 9.85 | | | | | |
| Cadmium | 594 | 8650 | 231 | 96.8 | 48.4 | 203 | 600 | 1463 | 1892 | 2160 | 2338 | | | | | |
| Chromium | 2118 | 7160 | 449 | 93.7 | 29.1 | 159 | 222 | 242 | | | | | | | | |
| Cobalt | 1769 | 8862 | 421 | 99.2 | 26.6 | 167 | 384 | 484 | 542 | 581 | 616 | 682 | 779 | 937 | | |
| Copper Pure | 1358 | 8933 | 385 | 401 | 117 | 482 | 413 | 393 | 379 | 366 | 352 | 339 | | | | |
| Commercial bronze (90% Cu, 10% Al) | 1293 | 8800 | 420 | 52 | 14 | 252 | 356 | 397 | 417 | 433 | 451 | 480 | | | | |
| Phosphor gear bronze (89% Cu, 11% Sn) | 1104 | 8780 | 355 | 54 | 17 | 785 | 42 | 52 | 59 | | | | | | | |
| Cartridge brass (70% Cu, 30% Zn) | 1188 | 8530 | 380 | 110 | 33.9 | 75 | 785 | 460 | 545 | 74 | | | | | | |
| Constantan (55% Cu, 45% Ni) | 1493 | 8920 | 384 | 23 | 6.71 | 17 | 41 | 65 | — | — | | | | | | |
| Germanium | 1211 | 5360 | 322 | 59.9 | 34.7 | 232 | 362 | 43.2 | 27.3 | 19.8 | 17.4 | 17.4 | | | | |
| | | | | | | 190 | 290 | 337 | 348 | 357 | 375 | 395 | | | | |

TABLE A.1 Continued

| Composition | Melting Point (K) | Properties at 300 K | | | | | Properties at Various Temperatures (K) | | | | | | | | | |
|---|-------------------|-----------------------------|------------------|---|---|------------------|---|---------------|------------------|---|---------------|------------------|---|---------------|------------------|---|
| | | ρ (kg/m ³) | c_p (J/kg · K) | k (W/m · K) | $\alpha \cdot 10^6$ (m ² /s) | 100 | 200 | 400 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 | |
| | | k (W/m · K) | c_p (J/kg · K) | $\alpha \cdot 10^6$ (m ² /s) | k (W/m · K) | c_p (J/kg · K) | $\alpha \cdot 10^6$ (m ² /s) | k (W/m · K) | c_p (J/kg · K) | $\alpha \cdot 10^6$ (m ² /s) | k (W/m · K) | c_p (J/kg · K) | $\alpha \cdot 10^6$ (m ² /s) | k (W/m · K) | c_p (J/kg · K) | $\alpha \cdot 10^6$ (m ² /s) |
| Gold | 1336 | 19300 | 129 | 317 | 127 | 327 | 323 | 311 | 298 | 284 | 270 | 255 | | | | |
| Iridium | 2720 | 22500 | 130 | 147 | 50.3 | 172 | 153 | 144 | 138 | 132 | 126 | 120 | 111 | | | |
| Iron | 1810 | 7870 | 447 | 80.2 | 23.1 | 134 | 94.0 | 69.5 | 54.7 | 43.3 | 32.8 | 28.3 | 32.1 | | | |
| Pure | | | | | | 216 | 384 | 490 | 574 | 680 | 975 | 609 | 654 | | | |
| Armco (99.75% pure) | | 7870 | 447 | 72.7 | 20.7 | 95.6 | 80.6 | 65.7 | 53.1 | 42.2 | 32.3 | 28.7 | 31.4 | | | |
| | | | | | | 215 | 384 | 490 | 574 | 680 | 975 | 609 | 654 | | | |
| Carbon steels | | | | | | | | | | | | | | | | |
| Plain carbon (Mn \leq 1%, Si \leq 0.1%) | | 7854 | 434 | 60.5 | 17.7 | | | 56.7 | 48.0 | 39.2 | 30.0 | | | | | |
| AISI 1010 | | 7832 | 434 | 63.9 | 18.8 | | | 487 | 559 | 685 | 1168 | | | | | |
| Carbon-silicon (Mn \leq 1%, 0.1% < Si \leq 0.6%) | | 7817 | 446 | 51.9 | 14.9 | | | 58.7 | 48.8 | 39.2 | 31.3 | | | | | |
| Carbon-manganese-silicon (1% < Mn \leq 1.65%, 0.1% < Si \leq 0.6%) | | 8131 | 434 | 41.0 | 11.6 | | | 487 | 49.8 | 44.0 | 29.3 | | | | | |
| Chromium (low) steels $\frac{1}{2}$ Cr- $\frac{1}{4}$ Mo-Si (0.18% C, 0.65% Cr, 0.23% Mo, 0.6% Si) | | 7822 | 444 | 37.7 | 10.9 | | | 501 | 582 | 699 | 971 | | | | | |
| 1 Cr- $\frac{1}{2}$ Mo (0.16% C, 1% Cr, 0.54% Mo, 0.39% Si) | | 7858 | 442 | 42.3 | 12.2 | | | 42.2 | 39.7 | 35.0 | 27.6 | | | | | |
| 1 Cr-V (0.2% C, 1.02% Cr, 0.15% V) | | 7836 | 443 | 48.9 | 14.1 | | | 487 | 559 | 685 | 1090 | | | | | |
| | | | | | | | | 38.2 | 36.7 | 33.3 | 26.9 | | | | | |
| | | | | | | | | 492 | 575 | 688 | 969 | | | | | |
| | | | | | | | | 42.0 | 39.1 | 34.5 | 27.4 | | | | | |
| | | | | | | | | 492 | 575 | 688 | 969 | | | | | |
| | | | | | | | | 46.8 | 42.1 | 36.3 | 28.2 | | | | | |
| | | | | | | | | 492 | 575 | 688 | 969 | | | | | |

TABLE A.1 Continued

| Composition | Melting Point (K) | Properties at 300 K | | | | | Properties at Various Temperatures (K) | | | | | | | | | |
|-------------|-------------------|-----------------------------|----------------|-------------|---|-----------------------------|--|------|------|------|------|------|------|------|------|--|
| | | ρ (kg/m ³) | c_p (J/kg·K) | k (W/m·K) | $\alpha \cdot 10^6$ (m ² /s) | k (W/m·K)/ c_p (J/kg·K) | | | | | | | | | | |
| | | | | | | 100 | 200 | 400 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 | |
| Titanium | 1953 | 4500 | 522 | 21.9 | 9.32 | 30.5 | 24.5 | 20.4 | 19.4 | 19.7 | 20.7 | 22.0 | 24.5 | | | |
| | | | | | | 300 | 465 | 551 | 591 | 633 | 675 | 620 | 686 | | | |
| Tungsten | 3660 | 19300 | 132 | 174 | 68.3 | 208 | 186 | 159 | 137 | 125 | 118 | 113 | 107 | 100 | 95 | |
| | | | | | | 87 | 122 | 137 | 142 | 145 | 148 | 152 | 157 | 167 | 176 | |
| Uranium | 1406 | 19070 | 116 | 27.6 | 12.5 | 21.7 | 25.1 | 29.6 | 34.0 | 38.8 | 43.9 | 49.0 | | | | |
| | | | | | | 94 | 108 | 125 | 146 | 176 | 180 | 161 | | | | |
| Vanadium | 2192 | 6100 | 489 | 30.7 | 10.3 | 35.8 | 31.3 | 31.3 | 33.3 | 35.7 | 38.2 | 40.8 | 44.6 | 50.9 | | |
| | | | | | | 258 | 430 | 515 | 540 | 563 | 597 | 645 | 714 | 867 | | |
| Zinc | 693 | 7140 | 389 | 116 | 41.8 | 117 | 118 | 111 | 103 | | | | | | | |
| | | | | | | 297 | 367 | 402 | 436 | | | | | | | |
| Zirconium | 2125 | 6570 | 278 | 22.7 | 12.4 | 33.2 | 25.2 | 21.6 | 20.7 | 21.6 | 23.7 | 26.0 | 28.8 | 33.0 | | |
| | | | | | | 205 | 264 | 300 | 322 | 342 | 362 | 344 | 344 | 344 | | |

^aAdapted from References 1–7.

TABLE A.2 Thermophysical Properties of Selected Nonmetallic Solids^a

| Composition | Melting Point (K) | Properties at 300 K | | | | | Properties at Various Temperatures (K) | | | | | | | | | |
|--|-------------------|-----------------------------|----------------|-------------|---|-------------|--|------|------|------|------|------|------|------|------|------|
| | | ρ (kg/m ³) | c_p (J/kg·K) | k (W/m·K) | $\alpha \cdot 10^6$ (m ² /s) | k (W/m·K) | 100 | 200 | 400 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 |
| Aluminum oxide, sapphire | 2323 | 3970 | 765 | 46 | 15.1 | 450 | — | 82 | 32.4 | 18.9 | 13.0 | 10.5 | — | — | — | — |
| Aluminum oxide, polycrystalline | 2323 | 3970 | 765 | 36.0 | 11.9 | 133 | — | 55 | 26.4 | 15.8 | 10.4 | 7.85 | 6.55 | 5.66 | 6.00 | |
| Beryllium oxide | 2725 | 3000 | 1030 | 272 | 88.0 | — | — | — | 940 | 1110 | 1180 | 1225 | — | — | — | |
| Boron | 2573 | 2500 | 1105 | 27.6 | 9.99 | 190 | — | 52.5 | 18.7 | 11.3 | 8.1 | 6.3 | 5.2 | 21.5 | 15 | |
| Boron fiber epoxy (30% vol) composite | 590 | 2080 | — | 1.60 | — | — | — | — | 1490 | 1880 | 2135 | 2350 | 2555 | 2145 | 2750 | |
| k , to fibers | | | | 2.29 | | 2.10 | | 2.23 | 2.28 | | | | | | | |
| k , \perp to fibers | | | | 0.59 | | 0.37 | | 0.49 | 0.60 | | | | | | | |
| c_p | | | 1122 | | | 364 | | 757 | 1431 | | | | | | | |
| Carbon | | | | | | | | | | | | | | | | |
| Amorphous | 1500 | 1950 | — | 1.60 | — | 0.67 | — | 1.18 | 1.89 | 2.19 | 2.37 | 2.53 | 2.84 | 3.48 | — | |
| Diamond, type IIa insulator | — | 3500 | 509 | 2300 | — | 10,000 | — | 4000 | 1540 | — | — | — | — | — | — | |
| Graphite, pyrolytic | 2273 | 2210 | — | 1950 | — | 4970 | — | 3230 | 1390 | 892 | 667 | 534 | 448 | 357 | 262 | |
| k , to layers | | | | 5.70 | | 16.8 | | 9.23 | 4.09 | 2.68 | 2.01 | 1.60 | 1.34 | 1.08 | 0.81 | |
| k , \perp to layers | | | | — | | 136 | | 411 | 992 | 1406 | 1650 | 1793 | 1890 | 1974 | 2043 | |
| c_p | | | 709 | | | — | | — | — | — | — | — | — | — | — | |
| Graphite fiber epoxy (25% vol) composite | 450 | 1400 | — | 11.1 | | 5.7 | | 8.7 | 13.0 | | | | | | | |
| k , heat flow to fibers | | | | 0.87 | | 0.46 | | 0.68 | 1.1 | | | | | | | |
| k , heat flow \perp to fibers | | | | — | | 337 | | 642 | 1216 | | | | | | | |
| c_p | | | 935 | | | — | | — | — | | | | | | | |
| Pyrocera ^m | 1623 | 2600 | 808 | 3.98 | 1.89 | 5.25 | — | 4.78 | 3.64 | 3.28 | 3.08 | 2.96 | 2.87 | 2.79 | — | |
| Corning 9606 | | | | — | | — | | — | 908 | 1038 | 1122 | 1197 | 1264 | 1498 | — | |

TABLE A.2 Continued

| Composition | Melting Point (K) | Properties at 300 K | | | | Properties at Various Temperatures (K) | | | | | | | | | | | |
|---|-------------------|-----------------------------|------------------|---------------|---|--|------|------|------|------|------|------|------|------|------|---|---|
| | | ρ (kg/m ³) | c_p (J/kg · K) | k (W/m · K) | $\alpha \cdot 10^6$ (m ² /s) | 100 | 200 | 400 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 | | |
| Silicon carbide | 3100 | 3160 | 675 | 490 | 230 | — | — | — | — | — | — | — | — | — | — | — | — |
| Silicon dioxide, crystalline (quartz) | 1883 | 2650 | — | 10.4 | — | — | 880 | 1050 | 1135 | — | 87 | 58 | 30 | — | — | — | — |
| | | | | 6.21 | — | — | — | — | — | — | — | — | — | — | — | — | — |
| k, \parallel to c axis | | | 745 | — | — | — | — | — | — | — | — | — | — | — | — | — | — |
| k, \perp to c axis | | | — | — | — | — | — | — | — | — | — | — | — | — | — | — | — |
| c_p | | | — | — | — | — | — | — | — | — | — | — | — | — | — | — | — |
| Silicon dioxide, polycrystalline (fused silica) | 1883 | 2220 | 745 | 1.38 | 0.834 | 0.69 | 1.14 | 1.51 | 1.75 | 2.17 | 2.87 | 4.00 | — | — | — | — | — |
| Silicon nitride | 2173 | 2400 | 691 | 16.0 | 9.65 | — | — | 13.9 | 11.3 | 9.88 | 8.76 | 8.00 | 7.16 | 6.20 | — | — | — |
| Sulfur | 392 | 2070 | 708 | 0.206 | 0.141 | 0.165 | 578 | 778 | 937 | 1063 | 1155 | 1226 | 1306 | 1377 | — | — | — |
| | | | | | | 403 | 606 | | | | | | | | | | |
| Thorium dioxide | 3573 | 9110 | 235 | 13 | 6.1 | — | — | 10.2 | 6.6 | 4.7 | 3.68 | 3.12 | 2.73 | 2.5 | — | — | — |
| | | | | | | — | — | 255 | 274 | 285 | 295 | 303 | 315 | 330 | — | — | — |
| Titanium dioxide, polycrystalline | 2133 | 4157 | 710 | 8.4 | 2.8 | — | — | 7.01 | 5.02 | 3.94 | 3.46 | 3.28 | — | — | — | — | — |
| | | | | | | — | — | 805 | 880 | 910 | 930 | 945 | — | — | — | — | — |

*Adapted from References 1, 2, 3 and 6.

TABLE A.3 Thermophysical Properties of Common Materials^a**Structural Building Materials**

| Description/Composition | Typical Properties at 300 K | | |
|---|--|---|---------------------------------------|
| | Density, ρ (kg/m ³) | Thermal Conductivity, k (W/m · K) | Specific Heat, c_p (J/kg · K) |
| Building Boards | | | |
| Asbestos–cement board | 1920 | 0.58 | — |
| Gypsum or plaster board | 800 | 0.17 | — |
| Plywood | 545 | 0.12 | 1215 |
| Sheathing, regular density | 290 | 0.055 | 1300 |
| Acoustic tile | 290 | 0.058 | 1340 |
| Hardboard, siding | 640 | 0.094 | 1170 |
| Hardboard, high density | 1010 | 0.15 | 1380 |
| Particle board, low density | 590 | 0.078 | 1300 |
| Particle board, high density | 1000 | 0.170 | 1300 |
| Woods | | | |
| Hardwoods (oak, maple) | 720 | 0.16 | 1255 |
| Softwoods (fir, pine) | 510 | 0.12 | 1380 |
| Masonry Materials | | | |
| Cement mortar | 1860 | 0.72 | 780 |
| Brick, common | 1920 | 0.72 | 835 |
| Brick, face | 2083 | 1.3 | — |
| Clay tile, hollow | | | |
| 1 cell deep, 10 cm thick | — | 0.52 | — |
| 3 cells deep, 30 cm thick | — | 0.69 | — |
| Concrete block, 3 oval cores | | | |
| Sand/gravel, 20 cm thick | — | 1.0 | — |
| Cinder aggregate, 20 cm thick | — | 0.67 | — |
| Concrete block, rectangular core | | | |
| 2 cores, 20 cm thick, 16 kg | — | 1.1 | — |
| Same with filled cores | — | 0.60 | — |
| Plastering Materials | | | |
| Cement plaster, sand aggregate | 1860 | 0.72 | — |
| Gypsum plaster, sand aggregate | 1680 | 0.22 | 1085 |
| Gypsum plaster, vermiculite aggregate | 720 | 0.25 | — |

TABLE A.3 Continued

Insulating Materials and Systems

| Description/Composition | Typical Properties at 300 K | | |
|---|--|---|---------------------------------------|
| | Density, ρ (kg/m ³) | Thermal Conductivity, k (W/m · K) | Specific Heat, c_p (J/kg · K) |
| Blanket and Batt | | | |
| Glass fiber, paper faced | 16 | 0.046 | — |
| | 28 | 0.038 | — |
| | 40 | 0.035 | — |
| Glass fiber, coated; duct liner | 32 | 0.038 | 835 |
| Board and Slab | | | |
| Cellular glass | 145 | 0.058 | 1000 |
| Glass fiber, organic bonded | 105 | 0.036 | 795 |
| Polystyrene, expanded | | | |
| Extruded (R-12) | 55 | 0.027 | 1210 |
| Molded beads | 16 | 0.040 | 1210 |
| Mineral fiberboard; roofing material | 265 | 0.049 | — |
| Wood, shredded/cemented | 350 | 0.087 | 1590 |
| Cork | 120 | 0.039 | 1800 |
| Loose Fill | | | |
| Cork, granulated | 160 | 0.045 | — |
| Diatomaceous silica, coarse | 350 | 0.069 | — |
| Powder | 400 | 0.091 | — |
| Diatomaceous silica, fine powder | 200 | 0.052 | — |
| | 275 | 0.061 | — |
| Glass fiber, poured or blown | 16 | 0.043 | 835 |
| Vermiculite, flakes | 80 | 0.068 | 835 |
| | 160 | 0.063 | 1000 |
| Formed/Foamed-in-Place | | | |
| Mineral wool granules with asbestos/inorganic binders, sprayed | 190 | 0.046 | — |
| Polyvinyl acetate cork mastic; sprayed or troweled | — | 0.100 | — |
| Urethane, two-part mixture; rigid foam | 70 | 0.026 | 1045 |
| Reflective | | | |
| Aluminum foil separating fluffy glass mats; 10–12 layers, evacuated; for cryogenic applications (150 K) | 40 | 0.00016 | — |
| Aluminum foil and glass paper laminate; 75–150 layers; evacuated; for cryogenic application (150 K) | 120 | 0.000017 | — |
| Typical silica powder, evacuated | 160 | 0.0017 | — |

TABLE A.3 Continued

Industrial Insulation (Continued)

| Description/ Composition | Maximum Service Temperature (K) | Typical Density (kg/m ³) | Typical Thermal Conductivity, k (W/m · K), at Various Temperatures (K) | | | | | | | | | | | | | | | |
|---|---------------------------------------|--|--|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-------|-----|--|----------------|
| | | | 200 | 215 | 230 | 240 | 255 | 270 | 285 | 300 | 310 | 365 | 420 | 530 | 645 | 750 | | |
| Cellular glass | 700 | 145 | | | 0.046 | 0.048 | 0.051 | 0.052 | 0.055 | 0.058 | 0.062 | 0.069 | 0.079 | | | | | |
| Diatomaceous silica | 1145 1310 | 345 385 | | | | | | | | | | | | | | | | 0.092 0.101 |
| Polystyrene, rigid Extruded (R-12) | 350 | 56 | 0.023 | 0.023 | 0.022 | 0.023 | 0.023 | 0.025 | 0.026 | 0.027 | 0.029 | | | | | | | |
| Extruded (R-12) | 350 | 35 | 0.023 | 0.023 | 0.023 | 0.025 | 0.025 | 0.026 | 0.027 | 0.029 | | | | | | | | |
| Molded beads | 350 | 16 | 0.026 | 0.029 | 0.030 | 0.033 | 0.035 | 0.036 | 0.038 | 0.040 | | | | | | | | |
| Rubber, rigid foamed | 340 | 70 | | | | | | 0.029 | 0.030 | 0.032 | 0.033 | | | | | | | |
| Insulating Cement Mineral fiber (rock, slag or glass) | | | | | | | | | | | | | | | | | | |
| With clay binder | 1255 | 430 | | | | | | | | | 0.071 | 0.079 | 0.088 | 0.105 | 0.123 | | | |
| With hydraulic setting binder | 922 | 560 | | | | | | | | | 0.108 | 0.115 | 0.123 | 0.137 | | | | |
| Loose Fill Cellulose, wood or paper pulp | — | 45 | | | | | | | 0.038 | 0.039 | 0.042 | | | | | | | |
| Perlite, expanded | — | 105 | 0.036 | 0.039 | 0.042 | 0.043 | 0.046 | 0.049 | 0.051 | 0.053 | 0.056 | | | | | | | |
| Vermiculite, expanded | — | 122 80 | | | 0.056 | 0.058 | 0.061 | 0.063 | 0.065 | 0.068 | 0.071 | | | | | | | |
| | | | | | 0.049 | 0.051 | 0.055 | 0.058 | 0.061 | 0.063 | 0.066 | | | | | | | |

TABLE A.3 Continued

Other Materials

| Description/ Composition | Temperature (K) | Density, ρ (kg/m ³) | Thermal Conductivity, k (W/m · K) | Specific Heat, c_p (J/kg · K) |
|--|--------------------|--|---|---------------------------------------|
| Asphalt | 300 | 2115 | 0.062 | 920 |
| Bakelite | 300 | 1300 | 1.4 | 1465 |
| Brick, refractory | | | | |
| Carborundum | 872 | — | 18.5 | — |
| | 1672 | — | 11.0 | — |
| Chrome brick | 473 | 3010 | 2.3 | 835 |
| | 823 | | 2.5 | |
| | 1173 | | 2.0 | |
| Diatomaceous silica, fired | 478 | — | 0.25 | — |
| | 1145 | — | 0.30 | |
| Fireclay, burnt 1600 K | 773 | 2050 | 1.0 | 960 |
| | 1073 | — | 1.1 | |
| | 1373 | — | 1.1 | |
| Fireclay, burnt 1725 K | 773 | 2325 | 1.3 | 960 |
| | 1073 | | 1.4 | |
| | 1373 | | 1.4 | |
| Fireclay brick | 478 | 2645 | 1.0 | 960 |
| | 922 | | 1.5 | |
| | 1478 | | 1.8 | |
| Magnesite | 478 | — | 3.8 | 1130 |
| | 922 | — | 2.8 | |
| | 1478 | | 1.9 | |
| Clay | 300 | 1460 | 1.3 | 880 |
| Coal, anthracite | 300 | 1350 | 0.26 | 1260 |
| Concrete (stone mix) | 300 | 2300 | 1.4 | 880 |
| Cotton | 300 | 80 | 0.06 | 1300 |
| Foodstuffs | | | | |
| Banana (75.7% water content) | 300 | 980 | 0.481 | 3350 |
| Apple, red (75% water content) | 300 | 840 | 0.513 | 3600 |
| Cake, batter | 300 | 720 | 0.223 | — |
| Cake, fully baked | 300 | 280 | 0.121 | — |
| Chicken meat, white (74.4% water content) | 198 | — | 1.60 | — |
| | 233 | — | 1.49 | |
| | 253 | | 1.35 | |
| | 263 | | 1.20 | |
| | 273 | | 0.476 | |
| | 283 | | 0.480 | |
| | 293 | | 0.489 | |
| Glass | | | | |
| Plate (soda lime) | 300 | 2500 | 1.4 | 750 |
| Pyrex | 300 | 2225 | 1.4 | 835 |

TABLE A.3 Continued

Other Materials (Continued)

| Description/ Composition | Temperature (K) | Density, ρ (kg/m ³) | Thermal Conductivity, k (W/m · K) | Specific Heat, c_p (J/kg · K) |
|-----------------------------|--------------------|--|---|---------------------------------------|
| Ice | 273 | 920 | 1.88 | 2040 |
| | 253 | — | 2.03 | 1945 |
| Leather (sole) | 300 | 998 | 0.159 | — |
| Paper | 300 | 930 | 0.180 | 1340 |
| Paraffin | 300 | 900 | 0.240 | 2890 |
| Rock | | | | |
| Granite, Barre | 300 | 2630 | 2.79 | 775 |
| Limestone, Salem | 300 | 2320 | 2.15 | 810 |
| Marble, Halston | 300 | 2680 | 2.80 | 830 |
| Quartzite, Sioux | 300 | 2640 | 5.38 | 1105 |
| Sandstone, Berea | 300 | 2150 | 2.90 | 745 |
| Rubber, vulcanized | | | | |
| Soft | 300 | 1100 | 0.13 | 2010 |
| Hard | 300 | 1190 | 0.16 | — |
| Sand | 300 | 1515 | 0.27 | 800 |
| Soil | 300 | 2050 | 0.52 | 1840 |
| Snow | 273 | 110 | 0.049 | — |
| | | 500 | 0.190 | — |
| Teflon | 300 | 2200 | 0.35 | — |
| | 400 | | 0.45 | — |
| Tissue, human | | | | |
| Skin | 300 | — | 0.37 | — |
| Fat layer (adipose) | 300 | — | 0.2 | — |
| Muscle | 300 | — | 0.5 | — |
| Wood, cross grain | | | | |
| Balsa | 300 | 140 | 0.055 | — |
| Cypress | 300 | 465 | 0.097 | — |
| Fir | 300 | 415 | 0.11 | 2720 |
| Oak | 300 | 545 | 0.17 | 2385 |
| Yellow pine | 300 | 640 | 0.15 | 2805 |
| White pine | 300 | 435 | 0.11 | — |
| Wood, radial | | | | |
| Oak | 300 | 545 | 0.19 | 2385 |
| Fir | 300 | 420 | 0.14 | 2720 |

^aAdapted from References 1 and 8–13.

TABLE A.4 Thermophysical Properties of Gases at Atmospheric Pressure^a

| T (K) | ρ (kg/m ³) | c_p (kJ/kg · K) | $\mu \cdot 10^7$ (N · s/m ²) | $\nu \cdot 10^6$ (m ² /s) | $k \cdot 10^3$ (W/m · K) | $\alpha \cdot 10^6$ (m ² /s) | Pr |
|---|--------------------------------|----------------------|---|---|-----------------------------|--|-------|
| Air, $\mathcal{M} = 28.97$ kg/kmol | | | | | | | |
| 100 | 3.5562 | 1.032 | 71.1 | 2.00 | 9.34 | 2.54 | 0.786 |
| 150 | 2.3364 | 1.012 | 103.4 | 4.426 | 13.8 | 5.84 | 0.758 |
| 200 | 1.7458 | 1.007 | 132.5 | 7.590 | 18.1 | 10.3 | 0.737 |
| 250 | 1.3947 | 1.006 | 159.6 | 11.44 | 22.3 | 15.9 | 0.720 |
| 300 | 1.1614 | 1.007 | 184.6 | 15.89 | 26.3 | 22.5 | 0.707 |
| 350 | 0.9950 | 1.009 | 208.2 | 20.92 | 30.0 | 29.9 | 0.700 |
| 400 | 0.8711 | 1.014 | 230.1 | 26.41 | 33.8 | 38.3 | 0.690 |
| 450 | 0.7740 | 1.021 | 250.7 | 32.39 | 37.3 | 47.2 | 0.686 |
| 500 | 0.6964 | 1.030 | 270.1 | 38.79 | 40.7 | 56.7 | 0.684 |
| 550 | 0.6329 | 1.040 | 288.4 | 45.57 | 43.9 | 66.7 | 0.683 |
| 600 | 0.5804 | 1.051 | 305.8 | 52.69 | 46.9 | 76.9 | 0.685 |
| 650 | 0.5356 | 1.063 | 322.5 | 60.21 | 49.7 | 87.3 | 0.690 |
| 700 | 0.4975 | 1.075 | 338.8 | 68.10 | 52.4 | 98.0 | 0.695 |
| 750 | 0.4643 | 1.087 | 354.6 | 76.37 | 54.9 | 109 | 0.702 |
| 800 | 0.4354 | 1.099 | 369.8 | 84.93 | 57.3 | 120 | 0.709 |
| 850 | 0.4097 | 1.110 | 384.3 | 93.80 | 59.6 | 131 | 0.716 |
| 900 | 0.3868 | 1.121 | 398.1 | 102.9 | 62.0 | 143 | 0.720 |
| 950 | 0.3666 | 1.131 | 411.3 | 112.2 | 64.3 | 155 | 0.723 |
| 1000 | 0.3482 | 1.141 | 424.4 | 121.9 | 66.7 | 168 | 0.726 |
| 1100 | 0.3166 | 1.159 | 449.0 | 141.8 | 71.5 | 195 | 0.728 |
| 1200 | 0.2902 | 1.175 | 473.0 | 162.9 | 76.3 | 224 | 0.728 |
| 1300 | 0.2679 | 1.189 | 496.0 | 185.1 | 82 | 257 | 0.719 |
| 1400 | 0.2488 | 1.207 | 530 | 213 | 91 | 303 | 0.703 |
| 1500 | 0.2322 | 1.230 | 557 | 240 | 100 | 350 | 0.685 |
| 1600 | 0.2177 | 1.248 | 584 | 268 | 106 | 390 | 0.688 |
| 1700 | 0.2049 | 1.267 | 611 | 298 | 113 | 435 | 0.685 |
| 1800 | 0.1935 | 1.286 | 637 | 329 | 120 | 482 | 0.683 |
| 1900 | 0.1833 | 1.307 | 663 | 362 | 128 | 534 | 0.677 |
| 2000 | 0.1741 | 1.337 | 689 | 396 | 137 | 589 | 0.672 |
| 2100 | 0.1658 | 1.372 | 715 | 431 | 147 | 646 | 0.667 |
| 2200 | 0.1582 | 1.417 | 740 | 468 | 160 | 714 | 0.655 |
| 2300 | 0.1513 | 1.478 | 766 | 506 | 175 | 783 | 0.647 |
| 2400 | 0.1448 | 1.558 | 792 | 547 | 196 | 869 | 0.630 |
| 2500 | 0.1389 | 1.665 | 818 | 589 | 222 | 960 | 0.613 |
| 3000 | 0.1135 | 2.726 | 955 | 841 | 486 | 1570 | 0.536 |
| Ammonia (NH₃), $\mathcal{M} = 17.03$ kg/kmol | | | | | | | |
| 300 | 0.6894 | 2.158 | 101.5 | 14.7 | 24.7 | 16.6 | 0.887 |
| 320 | 0.6448 | 2.170 | 109 | 16.9 | 27.2 | 19.4 | 0.870 |
| 340 | 0.6059 | 2.192 | 116.5 | 19.2 | 29.3 | 22.1 | 0.872 |
| 360 | 0.5716 | 2.221 | 124 | 21.7 | 31.6 | 24.9 | 0.872 |
| 380 | 0.5410 | 2.254 | 131 | 24.2 | 34.0 | 27.9 | 0.869 |

TABLE A.4 Continued

| T (K) | ρ (kg/m ³) | c_p (kJ/kg · K) | $\mu \cdot 10^7$ (N · s/m ²) | $\nu \cdot 10^6$ (m ² /s) | $k \cdot 10^3$ (W/m · K) | $\alpha \cdot 10^6$ (m ² /s) | Pr |
|--|--------------------------------|----------------------|---|---|-----------------------------|--|-------|
| Ammonia (NH₃) (continued) | | | | | | | |
| 400 | 0.5136 | 2.287 | 138 | 26.9 | 37.0 | 31.5 | 0.853 |
| 420 | 0.4888 | 2.322 | 145 | 29.7 | 40.4 | 35.6 | 0.833 |
| 440 | 0.4664 | 2.357 | 152.5 | 32.7 | 43.5 | 39.6 | 0.826 |
| 460 | 0.4460 | 2.393 | 159 | 35.7 | 46.3 | 43.4 | 0.822 |
| 480 | 0.4273 | 2.430 | 166.5 | 39.0 | 49.2 | 47.4 | 0.822 |
| 500 | 0.4101 | 2.467 | 173 | 42.2 | 52.5 | 51.9 | 0.813 |
| 520 | 0.3942 | 2.504 | 180 | 45.7 | 54.5 | 55.2 | 0.827 |
| 540 | 0.3795 | 2.540 | 186.5 | 49.1 | 57.5 | 59.7 | 0.824 |
| 560 | 0.3708 | 2.577 | 193 | 52.0 | 60.6 | 63.4 | 0.827 |
| 580 | 0.3533 | 2.613 | 199.5 | 56.5 | 63.8 | 69.1 | 0.817 |
| Carbon Dioxide (CO₂), $\mathcal{M} = 44.01$ kg/kmol | | | | | | | |
| 280 | 1.9022 | 0.830 | 140 | 7.36 | 15.20 | 9.63 | 0.765 |
| 300 | 1.7730 | 0.851 | 149 | 8.40 | 16.55 | 11.0 | 0.766 |
| 320 | 1.6609 | 0.872 | 156 | 9.39 | 18.05 | 12.5 | 0.754 |
| 340 | 1.5618 | 0.891 | 165 | 10.6 | 19.70 | 14.2 | 0.746 |
| 360 | 1.4743 | 0.908 | 173 | 11.7 | 21.2 | 15.8 | 0.741 |
| 380 | 1.3961 | 0.926 | 181 | 13.0 | 22.75 | 17.6 | 0.737 |
| 400 | 1.3257 | 0.942 | 190 | 14.3 | 24.3 | 19.5 | 0.737 |
| 450 | 1.1782 | 0.981 | 210 | 17.8 | 28.3 | 24.5 | 0.728 |
| 500 | 1.0594 | 1.02 | 231 | 21.8 | 32.5 | 30.1 | 0.725 |
| 550 | 0.9625 | 1.05 | 251 | 26.1 | 36.6 | 36.2 | 0.721 |
| 600 | 0.8826 | 1.08 | 270 | 30.6 | 40.7 | 42.7 | 0.717 |
| 650 | 0.8143 | 1.10 | 288 | 35.4 | 44.5 | 49.7 | 0.712 |
| 700 | 0.7564 | 1.13 | 305 | 40.3 | 48.1 | 56.3 | 0.717 |
| 750 | 0.7057 | 1.15 | 321 | 45.5 | 51.7 | 63.7 | 0.714 |
| 800 | 0.6614 | 1.17 | 337 | 51.0 | 55.1 | 71.2 | 0.716 |
| Carbon Monoxide (CO), $\mathcal{M} = 28.01$ kg/kmol | | | | | | | |
| 200 | 1.6888 | 1.045 | 127 | 7.52 | 17.0 | 9.63 | 0.781 |
| 220 | 1.5341 | 1.044 | 137 | 8.93 | 19.0 | 11.9 | 0.753 |
| 240 | 1.4055 | 1.043 | 147 | 10.5 | 20.6 | 14.1 | 0.744 |
| 260 | 1.2967 | 1.043 | 157 | 12.1 | 22.1 | 16.3 | 0.741 |
| 280 | 1.2038 | 1.042 | 166 | 13.8 | 23.6 | 18.8 | 0.733 |
| 300 | 1.1233 | 1.043 | 175 | 15.6 | 25.0 | 21.3 | 0.730 |
| 320 | 1.0529 | 1.043 | 184 | 17.5 | 26.3 | 23.9 | 0.730 |
| 340 | 0.9909 | 1.044 | 193 | 19.5 | 27.8 | 26.9 | 0.725 |
| 360 | 0.9357 | 1.045 | 202 | 21.6 | 29.1 | 29.8 | 0.725 |
| 380 | 0.8864 | 1.047 | 210 | 23.7 | 30.5 | 32.9 | 0.729 |
| 400 | 0.8421 | 1.049 | 218 | 25.9 | 31.8 | 36.0 | 0.719 |
| 450 | 0.7483 | 1.055 | 237 | 31.7 | 35.0 | 44.3 | 0.714 |
| 500 | 0.67352 | 1.065 | 254 | 37.7 | 38.1 | 53.1 | 0.710 |
| 550 | 0.61226 | 1.076 | 271 | 44.3 | 41.1 | 62.4 | 0.710 |
| 600 | 0.56126 | 1.088 | 286 | 51.0 | 44.0 | 72.1 | 0.707 |

TABLE A.4 Continued

| T (K) | ρ (kg/m ³) | c_p (kJ/kg · K) | $\mu \cdot 10^7$ (N · s/m ²) | $\nu \cdot 10^6$ (m ² /s) | $k \cdot 10^3$ (W/m · K) | $\alpha \cdot 10^6$ (m ² /s) | Pr |
|---|--------------------------------|----------------------|---|---|-----------------------------|--|-------|
| Carbon Monoxide (CO) (continued) | | | | | | | |
| 650 | 0.51806 | 1.101 | 301 | 58.1 | 47.0 | 82.4 | 0.705 |
| 700 | 0.48102 | 1.114 | 315 | 65.5 | 50.0 | 93.3 | 0.702 |
| 750 | 0.44899 | 1.127 | 329 | 73.3 | 52.8 | 104 | 0.702 |
| 800 | 0.42095 | 1.140 | 343 | 81.5 | 55.5 | 116 | 0.705 |
| Helium (He), $\mathcal{M} = 4.003$ kg/kmol | | | | | | | |
| 100 | 0.4871 | 5.193 | 96.3 | 19.8 | 73.0 | 28.9 | 0.686 |
| 120 | 0.4060 | 5.193 | 107 | 26.4 | 81.9 | 38.8 | 0.679 |
| 140 | 0.3481 | 5.193 | 118 | 33.9 | 90.7 | 50.2 | 0.676 |
| 160 | — | 5.193 | 129 | — | 99.2 | — | — |
| 180 | 0.2708 | 5.193 | 139 | 51.3 | 107.2 | 76.2 | 0.673 |
| 200 | — | 5.193 | 150 | — | 115.1 | — | — |
| 220 | 0.2216 | 5.193 | 160 | 72.2 | 123.1 | 107 | 0.675 |
| 240 | — | 5.193 | 170 | — | 130 | — | — |
| 260 | 0.1875 | 5.193 | 180 | 96.0 | 137 | 141 | 0.682 |
| 280 | — | 5.193 | 190 | — | 145 | — | — |
| 300 | 0.1625 | 5.193 | 199 | 122 | 152 | 180 | 0.680 |
| 350 | — | 5.193 | 221 | — | 170 | — | — |
| 400 | 0.1219 | 5.193 | 243 | 199 | 187 | 295 | 0.675 |
| 450 | — | 5.193 | 263 | — | 204 | — | — |
| 500 | 0.09754 | 5.193 | 283 | 290 | 220 | 434 | 0.668 |
| 550 | — | 5.193 | — | — | — | — | — |
| 600 | — | 5.193 | 320 | — | 252 | — | — |
| 650 | — | 5.193 | 332 | — | 264 | — | — |
| 700 | 0.06969 | 5.193 | 350 | 502 | 278 | 768 | 0.654 |
| 750 | — | 5.193 | 364 | — | 291 | — | — |
| 800 | — | 5.193 | 382 | — | 304 | — | — |
| 900 | — | 5.193 | 414 | — | 330 | — | — |
| 1000 | 0.04879 | 5.193 | 446 | 914 | 354 | 1400 | 0.654 |
| Hydrogen (H₂), $\mathcal{M} = 2.016$ kg/kmol | | | | | | | |
| 100 | 0.24255 | 11.23 | 42.1 | 17.4 | 67.0 | 24.6 | 0.707 |
| 150 | 0.16156 | 12.60 | 56.0 | 34.7 | 101 | 49.6 | 0.699 |
| 200 | 0.12115 | 13.54 | 68.1 | 56.2 | 131 | 79.9 | 0.704 |
| 250 | 0.09693 | 14.06 | 78.9 | 81.4 | 157 | 115 | 0.707 |
| 300 | 0.08078 | 14.31 | 89.6 | 111 | 183 | 158 | 0.701 |
| 350 | 0.06924 | 14.43 | 98.8 | 143 | 204 | 204 | 0.700 |
| 400 | 0.06059 | 14.48 | 108.2 | 179 | 226 | 258 | 0.695 |
| 450 | 0.05386 | 14.50 | 117.2 | 218 | 247 | 316 | 0.689 |
| 500 | 0.04848 | 14.52 | 126.4 | 261 | 266 | 378 | 0.691 |
| 550 | 0.04407 | 14.53 | 134.3 | 305 | 285 | 445 | 0.685 |

TABLE A.4 Continued

| T (K) | ρ (kg/m ³) | c_p (kJ/kg · K) | $\mu \cdot 10^7$ (N · s/m ²) | $\nu \cdot 10^6$ (m ² /s) | $k \cdot 10^3$ (W/m · K) | $\alpha \cdot 10^6$ (m ² /s) | Pr |
|---|--------------------------------|----------------------|---|---|-----------------------------|--|-------|
| Hydrogen (H₂) (continued) | | | | | | | |
| 600 | 0.04040 | 14.55 | 142.4 | 352 | 305 | 519 | 0.678 |
| 700 | 0.03463 | 14.61 | 157.8 | 456 | 342 | 676 | 0.675 |
| 800 | 0.03030 | 14.70 | 172.4 | 569 | 378 | 849 | 0.670 |
| 900 | 0.02694 | 14.83 | 186.5 | 692 | 412 | 1030 | 0.671 |
| 1000 | 0.02424 | 14.99 | 201.3 | 830 | 448 | 1230 | 0.673 |
| 1100 | 0.02204 | 15.17 | 213.0 | 966 | 488 | 1460 | 0.662 |
| 1200 | 0.02020 | 15.37 | 226.2 | 1120 | 528 | 1700 | 0.659 |
| 1300 | 0.01865 | 15.59 | 238.5 | 1279 | 568 | 1955 | 0.655 |
| 1400 | 0.01732 | 15.81 | 250.7 | 1447 | 610 | 2230 | 0.650 |
| 1500 | 0.01616 | 16.02 | 262.7 | 1626 | 655 | 2530 | 0.643 |
| 1600 | 0.0152 | 16.28 | 273.7 | 1801 | 697 | 2815 | 0.639 |
| 1700 | 0.0143 | 16.58 | 284.9 | 1992 | 742 | 3130 | 0.637 |
| 1800 | 0.0135 | 16.96 | 296.1 | 2193 | 786 | 3435 | 0.639 |
| 1900 | 0.0128 | 17.49 | 307.2 | 2400 | 835 | 3730 | 0.643 |
| 2000 | 0.0121 | 18.25 | 318.2 | 2630 | 878 | 3975 | 0.661 |
| Nitrogen (N₂), $M = 28.01$ kg/kmol | | | | | | | |
| 100 | 3.4388 | 1.070 | 68.8 | 2.00 | 9.58 | 2.60 | 0.768 |
| 150 | 2.2594 | 1.050 | 100.6 | 4.45 | 13.9 | 5.86 | 0.759 |
| 200 | 1.6883 | 1.043 | 129.2 | 7.65 | 18.3 | 10.4 | 0.736 |
| 250 | 1.3488 | 1.042 | 154.9 | 11.48 | 22.2 | 15.8 | 0.727 |
| 300 | 1.1233 | 1.041 | 178.2 | 15.86 | 25.9 | 22.1 | 0.716 |
| 350 | 0.9625 | 1.042 | 200.0 | 20.78 | 29.3 | 29.2 | 0.711 |
| 400 | 0.8425 | 1.045 | 220.4 | 26.16 | 32.7 | 37.1 | 0.704 |
| 450 | 0.7485 | 1.050 | 239.6 | 32.01 | 35.8 | 45.6 | 0.703 |
| 500 | 0.6739 | 1.056 | 257.7 | 38.24 | 38.9 | 54.7 | 0.700 |
| 550 | 0.6124 | 1.065 | 274.7 | 44.86 | 41.7 | 63.9 | 0.702 |
| 600 | 0.5615 | 1.075 | 290.8 | 51.79 | 44.6 | 73.9 | 0.701 |
| 700 | 0.4812 | 1.098 | 321.0 | 66.71 | 49.9 | 94.4 | 0.706 |
| 800 | 0.4211 | 1.122 | 349.1 | 82.90 | 54.8 | 116 | 0.715 |
| 900 | 0.3743 | 1.146 | 375.3 | 100.3 | 59.7 | 139 | 0.721 |
| 1000 | 0.3368 | 1.167 | 399.9 | 118.7 | 64.7 | 165 | 0.721 |
| 1100 | 0.3062 | 1.187 | 423.2 | 138.2 | 70.0 | 193 | 0.718 |
| 1200 | 0.2807 | 1.204 | 445.3 | 158.6 | 75.8 | 224 | 0.707 |
| 1300 | 0.2591 | 1.219 | 466.2 | 179.9 | 81.0 | 256 | 0.701 |
| Oxygen (O₂), $M = 32.00$ kg/kmol | | | | | | | |
| 100 | 3.945 | 0.962 | 76.4 | 1.94 | 9.25 | 2.44 | 0.796 |
| 150 | 2.585 | 0.921 | 114.8 | 4.44 | 13.8 | 5.80 | 0.766 |
| 200 | 1.930 | 0.915 | 147.5 | 7.64 | 18.3 | 10.4 | 0.737 |
| 250 | 1.542 | 0.915 | 178.6 | 11.58 | 22.6 | 16.0 | 0.723 |
| 300 | 1.284 | 0.920 | 207.2 | 16.14 | 26.8 | 22.7 | 0.711 |

TABLE A.4 Continued

| T (K) | ρ (kg/m ³) | c_p (kJ/kg · K) | $\mu \cdot 10^7$ (N · s/m ²) | $\nu \cdot 10^6$ (m ² /s) | $k \cdot 10^3$ (W/m · K) | $\alpha \cdot 10^6$ (m ² /s) | Pr |
|--|--------------------------------|----------------------|---|---|-----------------------------|--|-------|
| Oxygen (O₂) (continued) | | | | | | | |
| 350 | 1.100 | 0.929 | 233.5 | 21.23 | 29.6 | 29.0 | 0.733 |
| 400 | 0.9620 | 0.942 | 258.2 | 26.84 | 33.0 | 36.4 | 0.737 |
| 450 | 0.8554 | 0.956 | 281.4 | 32.90 | 36.3 | 44.4 | 0.741 |
| 500 | 0.7698 | 0.972 | 303.3 | 39.40 | 41.2 | 55.1 | 0.716 |
| 550 | 0.6998 | 0.988 | 324.0 | 46.30 | 44.1 | 63.8 | 0.726 |
| 600 | 0.6414 | 1.003 | 343.7 | 53.59 | 47.3 | 73.5 | 0.729 |
| 700 | 0.5498 | 1.031 | 380.8 | 69.26 | 52.8 | 93.1 | 0.744 |
| 800 | 0.4810 | 1.054 | 415.2 | 86.32 | 58.9 | 116 | 0.743 |
| 900 | 0.4275 | 1.074 | 447.2 | 104.6 | 64.9 | 141 | 0.740 |
| 1000 | 0.3848 | 1.090 | 477.0 | 124.0 | 71.0 | 169 | 0.733 |
| 1100 | 0.3498 | 1.103 | 505.5 | 144.5 | 75.8 | 196 | 0.736 |
| 1200 | 0.3206 | 1.115 | 532.5 | 166.1 | 81.9 | 229 | 0.725 |
| 1300 | 0.2960 | 1.125 | 588.4 | 188.6 | 87.1 | 262 | 0.721 |
| Water Vapor (Steam), $\mathcal{M} = 18.02$ kg/kmol | | | | | | | |
| 380 | 0.5863 | 2.060 | 127.1 | 21.68 | 24.6 | 20.4 | 1.06 |
| 400 | 0.5542 | 2.014 | 134.4 | 24.25 | 26.1 | 23.4 | 1.04 |
| 450 | 0.4902 | 1.980 | 152.5 | 31.11 | 29.9 | 30.8 | 1.01 |
| 500 | 0.4405 | 1.985 | 170.4 | 38.68 | 33.9 | 38.8 | 0.998 |
| 550 | 0.4005 | 1.997 | 188.4 | 47.04 | 37.9 | 47.4 | 0.993 |
| 600 | 0.3652 | 2.026 | 206.7 | 56.60 | 42.2 | 57.0 | 0.993 |
| 650 | 0.3380 | 2.056 | 224.7 | 66.48 | 46.4 | 66.8 | 0.996 |
| 700 | 0.3140 | 2.085 | 242.6 | 77.26 | 50.5 | 77.1 | 1.00 |
| 750 | 0.2931 | 2.119 | 260.4 | 88.84 | 54.9 | 88.4 | 1.00 |
| 800 | 0.2739 | 2.152 | 278.6 | 101.7 | 59.2 | 100 | 1.01 |
| 850 | 0.2579 | 2.186 | 296.9 | 115.1 | 63.7 | 113 | 1.02 |

^aAdapted from References 8, 14, and 15.

TABLE A.5 Thermophysical Properties of Saturated Fluids^a**Saturated Liquids**

| T (K) | ρ (kg/m ³) | c_p (kJ/kg · K) | $\mu \cdot 10^2$ (N · s/m ²) | $\nu \cdot 10^6$ (m ² /s) | $k \cdot 10^3$ (W/m · K) | $\alpha \cdot 10^7$ (m ² /s) | Pr | $\beta \cdot 10^3$ (K ⁻¹) |
|---|--------------------------------|----------------------|---|---|-----------------------------|--|--------|--|
| Engine Oil (Unused) | | | | | | | | |
| 273 | 899.1 | 1.796 | 385 | 4280 | 147 | 0.910 | 47,000 | 0.70 |
| 280 | 895.3 | 1.827 | 217 | 2430 | 144 | 0.880 | 27,500 | 0.70 |
| 290 | 890.0 | 1.868 | 99.9 | 1120 | 145 | 0.872 | 12,900 | 0.70 |
| 300 | 884.1 | 1.909 | 48.6 | 550 | 145 | 0.859 | 6400 | 0.70 |
| 310 | 877.9 | 1.951 | 25.3 | 288 | 145 | 0.847 | 3400 | 0.70 |
| 320 | 871.8 | 1.993 | 14.1 | 161 | 143 | 0.823 | 1965 | 0.70 |
| 330 | 865.8 | 2.035 | 8.36 | 96.6 | 141 | 0.800 | 1205 | 0.70 |
| 340 | 859.9 | 2.076 | 5.31 | 61.7 | 139 | 0.779 | 793 | 0.70 |
| 350 | 853.9 | 2.118 | 3.56 | 41.7 | 138 | 0.763 | 546 | 0.70 |
| 360 | 847.8 | 2.161 | 2.52 | 29.7 | 138 | 0.753 | 395 | 0.70 |
| 370 | 841.8 | 2.206 | 1.86 | 22.0 | 137 | 0.738 | 300 | 0.70 |
| 380 | 836.0 | 2.250 | 1.41 | 16.9 | 136 | 0.723 | 233 | 0.70 |
| 390 | 830.6 | 2.294 | 1.10 | 13.3 | 135 | 0.709 | 187 | 0.70 |
| 400 | 825.1 | 2.337 | 0.874 | 10.6 | 134 | 0.695 | 152 | 0.70 |
| 410 | 818.9 | 2.381 | 0.698 | 8.52 | 133 | 0.682 | 125 | 0.70 |
| 420 | 812.1 | 2.427 | 0.564 | 6.94 | 133 | 0.675 | 103 | 0.70 |
| 430 | 806.5 | 2.471 | 0.470 | 5.83 | 132 | 0.662 | 88 | 0.70 |
| Ethylene Glycol [C₂H₄(OH)₂] | | | | | | | | |
| 273 | 1130.8 | 2.294 | 6.51 | 57.6 | 242 | 0.933 | 617 | 0.65 |
| 280 | 1125.8 | 2.323 | 4.20 | 37.3 | 244 | 0.933 | 400 | 0.65 |
| 290 | 1118.8 | 2.368 | 2.47 | 22.1 | 248 | 0.936 | 236 | 0.65 |
| 300 | 1114.4 | 2.415 | 1.57 | 14.1 | 252 | 0.939 | 151 | 0.65 |
| 310 | 1103.7 | 2.460 | 1.07 | 9.65 | 255 | 0.939 | 103 | 0.65 |
| 320 | 1096.2 | 2.505 | 0.757 | 6.91 | 258 | 0.940 | 73.5 | 0.65 |
| 330 | 1089.5 | 2.549 | 0.561 | 5.15 | 260 | 0.936 | 55.0 | 0.65 |
| 340 | 1083.8 | 2.592 | 0.431 | 3.98 | 261 | 0.929 | 42.8 | 0.65 |
| 350 | 1079.0 | 2.637 | 0.342 | 3.17 | 261 | 0.917 | 34.6 | 0.65 |
| 360 | 1074.0 | 2.682 | 0.278 | 2.59 | 261 | 0.906 | 28.6 | 0.65 |
| 370 | 1066.7 | 2.728 | 0.228 | 2.14 | 262 | 0.900 | 23.7 | 0.65 |
| 373 | 1058.5 | 2.742 | 0.215 | 2.03 | 263 | 0.906 | 22.4 | 0.65 |
| Glycerin [C₃H₅(OH)₃] | | | | | | | | |
| 273 | 1276.0 | 2.261 | 1060 | 8310 | 282 | 0.977 | 85,000 | 0.47 |
| 280 | 1271.9 | 2.298 | 534 | 4200 | 284 | 0.972 | 43,200 | 0.47 |
| 290 | 1265.8 | 2.367 | 185 | 1460 | 286 | 0.955 | 15,300 | 0.48 |
| 300 | 1259.9 | 2.427 | 79.9 | 634 | 286 | 0.935 | 6780 | 0.48 |
| 310 | 1253.9 | 2.490 | 35.2 | 281 | 286 | 0.916 | 3060 | 0.49 |
| 320 | 1247.2 | 2.564 | 21.0 | 168 | 287 | 0.897 | 1870 | 0.50 |

TABLE A.5 Continued

Saturated Liquids (Continued)

| T (K) | ρ (kg/m ³) | c_p (kJ/kg · K) | $\mu \cdot 10^2$ (N · s/m ²) | $\nu \cdot 10^6$ (m ² /s) | $k \cdot 10^3$ (W/m · K) | $\alpha \cdot 10^7$ (m ² /s) | Pr | $\beta \cdot 10^3$ (K ⁻¹) |
|---|--------------------------------|----------------------|---|---|-----------------------------|--|--------|--|
| Refrigerant-134a (C₂H₂F₄) | | | | | | | | |
| 230 | 1426.8 | 1.249 | 0.04912 | 0.3443 | 112.1 | 0.629 | 5.5 | 2.02 |
| 240 | 1397.7 | 1.267 | 0.04202 | 0.3006 | 107.3 | 0.606 | 5.0 | 2.11 |
| 250 | 1367.9 | 1.287 | 0.03633 | 0.2656 | 102.5 | 0.583 | 4.6 | 2.23 |
| 260 | 1337.1 | 1.308 | 0.03166 | 0.2368 | 97.9 | 0.560 | 4.2 | 2.36 |
| 270 | 1305.1 | 1.333 | 0.02775 | 0.2127 | 93.4 | 0.537 | 4.0 | 2.53 |
| 280 | 1271.8 | 1.361 | 0.02443 | 0.1921 | 89.0 | 0.514 | 3.7 | 2.73 |
| 290 | 1236.8 | 1.393 | 0.02156 | 0.1744 | 84.6 | 0.491 | 3.5 | 2.98 |
| 300 | 1199.7 | 1.432 | 0.01905 | 0.1588 | 80.3 | 0.468 | 3.4 | 3.30 |
| 310 | 1159.9 | 1.481 | 0.01680 | 0.1449 | 76.1 | 0.443 | 3.3 | 3.73 |
| 320 | 1116.8 | 1.543 | 0.01478 | 0.1323 | 71.8 | 0.417 | 3.2 | 4.33 |
| 330 | 1069.1 | 1.627 | 0.01292 | 0.1209 | 67.5 | 0.388 | 3.1 | 5.19 |
| 340 | 1015.0 | 1.751 | 0.01118 | 0.1102 | 63.1 | 0.355 | 3.1 | 6.57 |
| 350 | 951.3 | 1.961 | 0.00951 | 0.1000 | 58.6 | 0.314 | 3.2 | 9.10 |
| 360 | 870.1 | 2.437 | 0.00781 | 0.0898 | 54.1 | 0.255 | 3.5 | 15.39 |
| 370 | 740.3 | 5.105 | 0.00580 | 0.0783 | 51.8 | 0.137 | 5.7 | 55.24 |
| Refrigerant-22 (CHClF₂) | | | | | | | | |
| 230 | 1416.0 | 1.087 | 0.03558 | 0.2513 | 114.5 | 0.744 | 3.4 | 2.05 |
| 240 | 1386.6 | 1.100 | 0.03145 | 0.2268 | 109.8 | 0.720 | 3.2 | 2.16 |
| 250 | 1356.3 | 1.117 | 0.02796 | 0.2062 | 105.2 | 0.695 | 3.0 | 2.29 |
| 260 | 1324.9 | 1.137 | 0.02497 | 0.1884 | 100.7 | 0.668 | 2.8 | 2.45 |
| 270 | 1292.1 | 1.161 | 0.02235 | 0.1730 | 96.2 | 0.641 | 2.7 | 2.63 |
| 280 | 1257.9 | 1.189 | 0.02005 | 0.1594 | 91.7 | 0.613 | 2.6 | 2.86 |
| 290 | 1221.7 | 1.223 | 0.01798 | 0.1472 | 87.2 | 0.583 | 2.5 | 3.15 |
| 300 | 1183.4 | 1.265 | 0.01610 | 0.1361 | 82.6 | 0.552 | 2.5 | 3.51 |
| 310 | 1142.2 | 1.319 | 0.01438 | 0.1259 | 78.1 | 0.518 | 2.4 | 4.00 |
| 320 | 1097.4 | 1.391 | 0.01278 | 0.1165 | 73.4 | 0.481 | 2.4 | 4.69 |
| 330 | 1047.5 | 1.495 | 0.01127 | 0.1075 | 68.6 | 0.438 | 2.5 | 5.75 |
| 340 | 990.1 | 1.665 | 0.00980 | 0.0989 | 63.6 | 0.386 | 2.6 | 7.56 |
| 350 | 920.1 | 1.997 | 0.00831 | 0.0904 | 58.3 | 0.317 | 2.8 | 11.35 |
| 360 | 823.4 | 3.001 | 0.00668 | 0.0811 | 53.1 | 0.215 | 3.8 | 23.88 |
| Mercury (Hg) | | | | | | | | |
| 273 | 13,595 | 0.1404 | 0.1688 | 0.1240 | 8180 | 42.85 | 0.0290 | 0.181 |
| 300 | 13,529 | 0.1393 | 0.1523 | 0.1125 | 8540 | 45.30 | 0.0248 | 0.181 |
| 350 | 13,407 | 0.1377 | 0.1309 | 0.0976 | 9180 | 49.75 | 0.0196 | 0.181 |
| 400 | 13,287 | 0.1365 | 0.1171 | 0.0882 | 9800 | 54.05 | 0.0163 | 0.181 |
| 450 | 13,167 | 0.1357 | 0.1075 | 0.0816 | 10,400 | 58.10 | 0.0140 | 0.181 |
| 500 | 13,048 | 0.1353 | 0.1007 | 0.0771 | 10,950 | 61.90 | 0.0125 | 0.182 |
| 550 | 12,929 | 0.1352 | 0.0953 | 0.0737 | 11,450 | 65.55 | 0.0112 | 0.184 |
| 600 | 12,809 | 0.1355 | 0.0911 | 0.0711 | 11,950 | 68.80 | 0.0103 | 0.187 |

TABLE A.5 Continued

Saturated Liquid–Vapor, 1 atm^b

| Fluid | T_{sat} (K) | h_{fg} (kJ/kg) | ρ_f (kg/m ³) | ρ_g (kg/m ³) | $\sigma \cdot 10^3$ (N/m) |
|--------------------|-------------------------|---------------------|----------------------------------|----------------------------------|------------------------------|
| Ethanol | 351 | 846 | 757 | 1.44 | 17.7 |
| Ethylene glycol | 470 | 812 | 1111 ^c | — | 32.7 |
| Glycerin | 563 | 974 | 1260 ^c | — | 63.0 ^c |
| Mercury | 630 | 301 | 12,740 | 3.90 | 417 |
| Refrigerant R-134a | 247 | 217 | 1377 | 5.26 | 15.4 |
| Refrigerant R-22 | 232 | 234 | 1409 | 4.70 | 18.1 |

^aAdapted from References 15–19.^bAdapted from References 8, 20, and 21.^cProperty value corresponding to 300 K.

TABLE A.6 Thermophysical Properties of Saturated Water^a

| Temperature, T (K) | Pressure, p (bar) ^b | Specific Volume (m ³ /kg) | | Heat of Vaporization, h_{fg} (kJ/kg) | Specific Heat (kJ/kg · K) | | Viscosity (N · s/m ²) | | Thermal Conductivity (W/m · K) | | Prandtl Number | | Surface Tension, $\sigma_f \cdot 10^3$ (N/m) | Expansion Coefficient, $\beta_f \cdot 10^6$ (K ⁻¹) | Temperature, T (K) |
|-------------------------|-------------------------------------|---|-------|--|------------------------------|-----------|--------------------------------------|--------------------|-----------------------------------|------------------|----------------|--------|--|--|-------------------------|
| | | $v_f \cdot 10^3$ | v_g | | $c_{p,f}$ | $c_{p,g}$ | $\mu_f \cdot 10^6$ | $\mu_g \cdot 10^6$ | $k_f \cdot 10^3$ | $k_g \cdot 10^3$ | Pr_f | Pr_g | | | |
| 273.15 | 0.00611 | 1.000 | 206.3 | 2502 | 4.217 | 1.854 | 1750 | 8.02 | 18.2 | 12.99 | 0.815 | 75.5 | -68.05 | 273.15 | |
| 275 | 0.00697 | 1.000 | 181.7 | 2497 | 4.211 | 1.855 | 1652 | 8.09 | 18.3 | 12.22 | 0.817 | 75.3 | -32.74 | 275 | |
| 280 | 0.00990 | 1.000 | 130.4 | 2485 | 4.198 | 1.858 | 1422 | 8.29 | 18.6 | 10.26 | 0.825 | 74.8 | 46.04 | 280 | |
| 285 | 0.01387 | 1.000 | 99.4 | 2473 | 4.189 | 1.861 | 1225 | 8.49 | 18.9 | 8.81 | 0.833 | 74.3 | 114.1 | 285 | |
| 290 | 0.01917 | 1.001 | 69.7 | 2461 | 4.184 | 1.864 | 1080 | 8.69 | 19.3 | 7.56 | 0.841 | 73.7 | 174.0 | 290 | |
| 295 | 0.02617 | 1.002 | 51.94 | 2449 | 4.181 | 1.868 | 959 | 8.89 | 19.5 | 6.62 | 0.849 | 72.7 | 227.5 | 295 | |
| 300 | 0.03531 | 1.003 | 39.13 | 2438 | 4.179 | 1.872 | 855 | 9.09 | 19.6 | 5.83 | 0.857 | 71.7 | 276.1 | 300 | |
| 305 | 0.04712 | 1.005 | 29.74 | 2426 | 4.178 | 1.877 | 769 | 9.29 | 20.1 | 5.20 | 0.865 | 70.9 | 320.6 | 305 | |
| 310 | 0.06221 | 1.007 | 22.93 | 2414 | 4.178 | 1.882 | 695 | 9.49 | 20.4 | 4.62 | 0.873 | 70.0 | 361.9 | 310 | |
| 315 | 0.08132 | 1.009 | 17.82 | 2402 | 4.179 | 1.888 | 631 | 9.69 | 20.7 | 4.16 | 0.883 | 69.2 | 400.4 | 315 | |
| 320 | 0.1053 | 1.011 | 13.98 | 2390 | 4.180 | 1.895 | 577 | 9.89 | 21.0 | 3.77 | 0.894 | 68.3 | 436.7 | 320 | |
| 325 | 0.1351 | 1.013 | 11.06 | 2378 | 4.182 | 1.903 | 528 | 10.09 | 21.3 | 3.42 | 0.901 | 67.5 | 471.2 | 325 | |
| 330 | 0.1719 | 1.016 | 8.82 | 2366 | 4.184 | 1.911 | 489 | 10.29 | 21.7 | 3.15 | 0.908 | 66.6 | 504.0 | 330 | |
| 335 | 0.2167 | 1.018 | 7.09 | 2354 | 4.186 | 1.920 | 453 | 10.49 | 22.0 | 2.88 | 0.916 | 65.8 | 535.5 | 335 | |
| 340 | 0.2713 | 1.021 | 5.74 | 2342 | 4.188 | 1.930 | 420 | 10.69 | 22.3 | 2.66 | 0.925 | 64.9 | 566.0 | 340 | |
| 345 | 0.3372 | 1.024 | 4.683 | 2329 | 4.191 | 1.941 | 389 | 10.89 | 22.6 | 2.45 | 0.933 | 64.1 | 595.4 | 345 | |
| 350 | 0.4163 | 1.027 | 3.846 | 2317 | 4.195 | 1.954 | 365 | 11.09 | 23.0 | 2.29 | 0.942 | 63.2 | 624.2 | 350 | |
| 355 | 0.5100 | 1.030 | 3.180 | 2304 | 4.199 | 1.968 | 343 | 11.29 | 23.3 | 2.14 | 0.951 | 62.3 | 652.3 | 355 | |
| 360 | 0.6209 | 1.034 | 2.645 | 2291 | 4.203 | 1.983 | 324 | 11.49 | 23.7 | 2.02 | 0.960 | 61.4 | 697.9 | 360 | |
| 365 | 0.7514 | 1.038 | 2.212 | 2278 | 4.209 | 1.999 | 306 | 11.69 | 24.1 | 1.91 | 0.969 | 60.5 | 707.1 | 365 | |
| 370 | 0.9040 | 1.041 | 1.861 | 2265 | 4.214 | 2.017 | 289 | 11.89 | 24.5 | 1.80 | 0.978 | 59.5 | 728.7 | 370 | |
| 373.15 | 1.0133 | 1.044 | 1.679 | 2257 | 4.217 | 2.029 | 279 | 12.02 | 24.8 | 1.76 | 0.984 | 58.9 | 750.1 | 373.15 | |
| 375 | 1.0815 | 1.045 | 1.574 | 2252 | 4.220 | 2.036 | 274 | 12.09 | 24.9 | 1.70 | 0.987 | 58.6 | 761 | 375 | |
| 380 | 1.2869 | 1.049 | 1.337 | 2239 | 4.226 | 2.057 | 260 | 12.29 | 25.4 | 1.61 | 0.999 | 57.6 | 788 | 380 | |
| 385 | 1.5233 | 1.053 | 1.142 | 2225 | 4.232 | 2.080 | 248 | 12.49 | 25.8 | 1.53 | 1.004 | 56.6 | 814 | 385 | |
| 390 | 1.794 | 1.058 | 0.980 | 2212 | 4.239 | 2.104 | 237 | 12.69 | 26.3 | 1.47 | 1.013 | 55.6 | 841 | 390 | |
| 400 | 2.455 | 1.067 | 0.731 | 2183 | 4.256 | 2.158 | 217 | 13.05 | 27.2 | 1.34 | 1.033 | 53.6 | 896 | 400 | |
| 410 | 3.302 | 1.077 | 0.553 | 2153 | 4.278 | 2.221 | 200 | 13.42 | 28.2 | 1.24 | 1.054 | 51.5 | 952 | 410 | |
| 420 | 4.370 | 1.088 | 0.425 | 2123 | 4.302 | 2.291 | 185 | 13.79 | 29.8 | 1.16 | 1.075 | 49.4 | 1010 | 420 | |
| 430 | 5.699 | 1.099 | 0.331 | 2091 | 4.331 | 2.369 | 173 | 14.14 | 30.4 | 1.09 | 1.10 | 47.2 | 1010 | 430 | |

TABLE A.6 Continued

| Temperature, T (K) | Pressure, p (bar) ^b | Specific Volume (m ³ /kg) | | Heat of Vaporization, h_{fg} (kJ/kg) | Specific Heat (kJ/kg·K) | | Viscosity (N·s/m ²) | | Thermal Conductivity (W/m·K) | | Prandtl Number | | Surface Tension, $\sigma_f \cdot 10^3$ (N/m) | Expansion Coefficient, $\beta_f \cdot 10^6$ (K ⁻¹) | Temperature, T (K) |
|-------------------------|-------------------------------------|---|--------|--|----------------------------|-----------|------------------------------------|--------------------|---------------------------------|------------------|----------------|--------|--|--|-------------------------|
| | | $v_f \cdot 10^3$ | v_g | | $c_{p,f}$ | $c_{p,g}$ | $\mu_f \cdot 10^6$ | $\mu_g \cdot 10^6$ | $k_f \cdot 10^3$ | $k_g \cdot 10^3$ | Pr_f | Pr_g | | | |
| 440 | 7.333 | 1.110 | 0.261 | 2059 | 4.36 | 2.46 | 162 | 14.50 | 682 | 31.7 | 1.04 | 1.12 | 45.1 | — | 440 |
| 450 | 9.319 | 1.123 | 0.208 | 2024 | 4.40 | 2.56 | 152 | 14.85 | 678 | 33.1 | 0.99 | 1.14 | 42.9 | — | 450 |
| 460 | 11.71 | 1.137 | 0.167 | 1989 | 4.44 | 2.68 | 143 | 15.19 | 673 | 34.6 | 0.95 | 1.17 | 40.7 | — | 460 |
| 470 | 14.55 | 1.152 | 0.136 | 1951 | 4.48 | 2.79 | 136 | 15.54 | 667 | 36.3 | 0.92 | 1.20 | 38.5 | — | 470 |
| 480 | 17.90 | 1.167 | 0.111 | 1912 | 4.53 | 2.94 | 129 | 15.88 | 660 | 38.1 | 0.89 | 1.23 | 36.2 | — | 480 |
| 490 | 21.83 | 1.184 | 0.0922 | 1870 | 4.59 | 3.10 | 124 | 16.23 | 651 | 40.1 | 0.87 | 1.25 | 33.9 | — | 490 |
| 500 | 26.40 | 1.203 | 0.0766 | 1825 | 4.66 | 3.27 | 118 | 16.59 | 642 | 42.3 | 0.86 | 1.28 | 31.6 | — | 500 |
| 510 | 31.66 | 1.222 | 0.0631 | 1779 | 4.74 | 3.47 | 113 | 16.95 | 631 | 44.7 | 0.85 | 1.31 | 29.3 | — | 510 |
| 520 | 37.70 | 1.244 | 0.0525 | 1730 | 4.84 | 3.70 | 108 | 17.33 | 621 | 47.5 | 0.84 | 1.35 | 26.9 | — | 520 |
| 530 | 44.58 | 1.268 | 0.0445 | 1679 | 4.95 | 3.96 | 104 | 17.72 | 608 | 50.6 | 0.85 | 1.39 | 24.5 | — | 530 |
| 540 | 52.38 | 1.294 | 0.0375 | 1622 | 5.08 | 4.27 | 101 | 18.1 | 594 | 54.0 | 0.86 | 1.43 | 22.1 | — | 540 |
| 550 | 61.19 | 1.323 | 0.0317 | 1564 | 5.24 | 4.64 | 97 | 18.6 | 580 | 58.3 | 0.87 | 1.47 | 19.7 | — | 550 |
| 560 | 71.08 | 1.355 | 0.0269 | 1499 | 5.43 | 5.09 | 94 | 19.1 | 563 | 63.7 | 0.90 | 1.52 | 17.3 | — | 560 |
| 570 | 82.16 | 1.392 | 0.0228 | 1429 | 5.68 | 5.67 | 91 | 19.7 | 548 | 76.7 | 0.94 | 1.59 | 15.0 | — | 570 |
| 580 | 94.51 | 1.433 | 0.0193 | 1353 | 6.00 | 6.40 | 88 | 20.4 | 528 | 76.7 | 0.99 | 1.68 | 12.8 | — | 580 |
| 590 | 108.3 | 1.482 | 0.0163 | 1274 | 6.41 | 7.35 | 84 | 21.5 | 513 | 84.1 | 1.05 | 1.84 | 10.5 | — | 590 |
| 600 | 123.5 | 1.541 | 0.0137 | 1176 | 7.00 | 8.75 | 81 | 22.7 | 497 | 92.9 | 1.14 | 2.15 | 8.4 | — | 600 |
| 610 | 137.3 | 1.612 | 0.0115 | 1068 | 7.85 | 11.1 | 77 | 24.1 | 467 | 103 | 1.30 | 2.60 | 6.3 | — | 610 |
| 620 | 159.1 | 1.705 | 0.0094 | 941 | 9.35 | 15.4 | 72 | 25.9 | 444 | 114 | 1.52 | 3.46 | 4.5 | — | 620 |
| 625 | 169.1 | 1.778 | 0.0085 | 858 | 10.6 | 18.3 | 70 | 27.0 | 430 | 121 | 1.65 | 4.20 | 3.5 | — | 625 |
| 630 | 179.7 | 1.856 | 0.0075 | 781 | 12.6 | 22.1 | 67 | 28.0 | 412 | 130 | 2.0 | 4.8 | 2.6 | — | 630 |
| 635 | 190.9 | 1.935 | 0.0066 | 683 | 16.4 | 27.6 | 64 | 30.0 | 392 | 141 | 2.7 | 6.0 | 1.5 | — | 635 |
| 640 | 202.7 | 2.075 | 0.0057 | 560 | 26 | 42 | 59 | 32.0 | 367 | 155 | 4.2 | 9.6 | 0.8 | — | 640 |
| 645 | 215.2 | 2.351 | 0.0045 | 361 | 90 | — | 54 | 37.0 | 331 | 178 | 12 | 26 | 0.1 | — | 645 |
| 647.3 ^c | 221.2 | 3.170 | 0.0032 | 0 | ∞ | ∞ | 45 | 45.0 | 238 | 238 | ∞ | ∞ | 0.0 | — | 647.3 ^c |

^aAdapted from Reference 22.^b1 bar = 10⁵ N/m².^cCritical temperature.

TABLE A.7 Thermophysical Properties of Liquid Metals^a

| Composition | Melting Point (K) | <i>T</i> (K) | ρ (kg/m ³) | c_p (kJ/kg · K) | $\nu \cdot 10^7$ (m ² /s) | <i>k</i> (W/m · K) | $\alpha \cdot 10^5$ (m ² /s) | <i>Pr</i> |
|------------------------|-------------------|--------------|-----------------------------|-------------------|--------------------------------------|--------------------|---|-----------|
| Bismuth | 544 | 589 | 10,010 | 0.1444 | 1.617 | 16.4 | 1.138 | 0.0142 |
| | | 811 | 9738 | 0.1545 | 1.133 | 15.6 | 1.035 | 0.0110 |
| | | 1033 | 9454 | 0.1645 | 0.8343 | 15.6 | 1.001 | 0.0083 |
| Lead | 600 | 644 | 10,540 | 0.159 | 2.276 | 16.1 | 1.084 | 0.024 |
| | | 755 | 10,412 | 0.155 | 1.849 | 15.6 | 1.223 | 0.017 |
| | | 977 | 10,140 | — | 1.347 | 14.9 | — | — |
| Potassium | 337 | 422 | 807.3 | 0.80 | 4.608 | 45.0 | 6.99 | 0.0066 |
| | | 700 | 741.7 | 0.75 | 2.397 | 39.5 | 7.07 | 0.0034 |
| | | 977 | 674.4 | 0.75 | 1.905 | 33.1 | 6.55 | 0.0029 |
| Sodium | 371 | 373 | 928.0 | 1.38 | 7.532 | 86.0 | 6.69 | 0.011 |
| | | 644 | 860.2 | 1.30 | 3.270 | 72.3 | 6.48 | 0.0051 |
| | | 977 | 778.5 | 1.26 | 2.285 | 59.7 | 6.12 | 0.0037 |
| NaK, (56%/44%) | 292 | 366 | 887.4 | 1.130 | 6.522 | 25.6 | 2.552 | 0.026 |
| | | 644 | 821.7 | 1.055 | 2.871 | 27.5 | 3.17 | 0.0091 |
| | | 977 | 740.1 | 1.043 | 2.174 | 28.9 | 3.74 | 0.0058 |
| NaK, (22%/78%) | 262 | 366 | 849.0 | 0.946 | 5.797 | 24.4 | 3.05 | 0.019 |
| | | 672 | 775.3 | 0.879 | 2.666 | 26.7 | 3.92 | 0.0068 |
| | | 1033 | 690.4 | 0.883 | 2.118 | — | — | — |
| PbBi, (44.5%/55.5%) | 398 | 422 | 10,524 | 0.147 | — | 9.05 | 0.586 | — |
| | | 644 | 10,236 | 0.147 | 1.496 | 11.86 | 0.790 | 0.189 |
| | | 922 | 9835 | — | 1.171 | — | — | — |
| Mercury | 234 | | | | See Table A.5 | | | |

^aAdapted from Reference 23.

TABLE A.8 Binary Diffusion Coefficients at One Atmosphere^{a,b}

| Substance A | Substance B | T (K) | D_{AB} (m ² /s) |
|-------------------------|------------------|----------|---------------------------------|
| Gases | | | |
| NH ₃ | Air | 298 | 0.28×10^{-4} |
| H ₂ O | Air | 298 | 0.26×10^{-4} |
| CO ₂ | Air | 298 | 0.16×10^{-4} |
| H ₂ | Air | 298 | 0.41×10^{-4} |
| O ₂ | Air | 298 | 0.21×10^{-4} |
| Acetone | Air | 273 | 0.11×10^{-4} |
| Benzene | Air | 298 | 0.88×10^{-5} |
| Naphthalene | Air | 300 | 0.62×10^{-5} |
| Ar | N ₂ | 293 | 0.19×10^{-4} |
| H ₂ | O ₂ | 273 | 0.70×10^{-4} |
| H ₂ | N ₂ | 273 | 0.68×10^{-4} |
| H ₂ | CO ₂ | 273 | 0.55×10^{-4} |
| CO ₂ | N ₂ | 293 | 0.16×10^{-4} |
| CO ₂ | O ₂ | 273 | 0.14×10^{-4} |
| O ₂ | N ₂ | 273 | 0.18×10^{-4} |
| Dilute Solutions | | | |
| Caffeine | H ₂ O | 298 | 0.63×10^{-9} |
| Ethanol | H ₂ O | 298 | 0.12×10^{-8} |
| Glucose | H ₂ O | 298 | 0.69×10^{-9} |
| Glycerol | H ₂ O | 298 | 0.94×10^{-9} |
| Acetone | H ₂ O | 298 | 0.13×10^{-8} |
| CO ₂ | H ₂ O | 298 | 0.20×10^{-8} |
| O ₂ | H ₂ O | 298 | 0.24×10^{-8} |
| H ₂ | H ₂ O | 298 | 0.63×10^{-8} |
| N ₂ | H ₂ O | 298 | 0.26×10^{-8} |
| Solids | | | |
| O ₂ | Rubber | 298 | 0.21×10^{-9} |
| N ₂ | Rubber | 298 | 0.15×10^{-9} |
| CO ₂ | Rubber | 298 | 0.11×10^{-9} |
| He | SiO ₂ | 293 | 0.4×10^{-13} |
| H ₂ | Fe | 293 | 0.26×10^{-12} |
| Cd | Cu | 293 | 0.27×10^{-18} |
| Al | Cu | 293 | 0.13×10^{-33} |

^aAdapted with permission from References 24, 25, and 26.

^bAssuming ideal gas behavior, the pressure and temperature dependence of the diffusion coefficient for a binary mixture of gases may be estimated from the relation

$$D_{AB} \propto p^{-1} T^{3/2}$$

TABLE A.9 Henry's Constant for Selected Gases in Water at Moderate Pressure^a

| $H = p_{A,i}/x_{A,i}$ (bar) | | | | | | | | |
|-----------------------------|-----------------|-----------------|------------------|-----------------|-----------------|-----------------|----------------|----------------|
| T (K) | NH ₃ | Cl ₂ | H ₂ S | SO ₂ | CO ₂ | CH ₄ | O ₂ | H ₂ |
| 273 | 21 | 265 | 260 | 165 | 710 | 22,880 | 25,500 | 58,000 |
| 280 | 23 | 365 | 335 | 210 | 960 | 27,800 | 30,500 | 61,500 |
| 290 | 26 | 480 | 450 | 315 | 1300 | 35,200 | 37,600 | 66,500 |
| 300 | 30 | 615 | 570 | 440 | 1730 | 42,800 | 45,700 | 71,600 |
| 310 | — | 755 | 700 | 600 | 2175 | 50,000 | 52,500 | 76,000 |
| 320 | — | 860 | 835 | 800 | 2650 | 56,300 | 56,800 | 78,600 |
| 323 | — | 890 | 870 | 850 | 2870 | 58,000 | 58,000 | 79,000 |

^aAdapted with permission from Reference 27.**TABLE A.10** The Solubility of Selected Gases and Solids^a

| Gas | Solid | T (K) | $S = C_{A,i}/p_{A,i}$ (kmol/m ³ · bar) |
|-----------------|------------------|------------|--|
| O ₂ | Rubber | 298 | 3.12×10^{-3} |
| N ₂ | Rubber | 298 | 1.56×10^{-3} |
| CO ₂ | Rubber | 298 | 40.15×10^{-3} |
| He | SiO ₂ | 293 | 0.45×10^{-3} |
| H ₂ | Ni | 358 | 9.01×10^{-3} |

^aData from Reference 26.

TABLE A.11 Total, Normal (n) or Hemispherical (h) Emissivity of Selected Surfaces

| Description/Composition | Emissivity, ϵ_n or ϵ_h , at Various Temperatures (K) | | | | | | | | | | | |
|---------------------------|--|------|------|------|------|------|------|------|------|------|------|------|
| | 100 | 200 | 300 | 400 | 600 | 800 | 1000 | 1200 | 1500 | 2000 | 2500 | |
| Aluminum | | | | | | | | | | | | |
| Highly polished, film | (h) | 0.02 | 0.03 | 0.04 | 0.05 | 0.06 | | | | | | |
| Foil, bright | (h) | 0.06 | 0.06 | 0.07 | | | | | | | | |
| Anodized | (h) | | | 0.82 | 0.76 | | | | | | | |
| Chromium | | | | | | | | | | | | |
| Polished or plated | (n) | 0.05 | 0.07 | 0.10 | 0.12 | 0.14 | | | | | | |
| Copper | | | | | | | | | | | | |
| Highly polished | (h) | | | 0.03 | 0.03 | 0.04 | 0.04 | 0.04 | | | | |
| Stably oxidized | (h) | | | | | 0.50 | 0.58 | 0.80 | | | | |
| Gold | | | | | | | | | | | | |
| Highly polished or film | (h) | 0.01 | 0.02 | 0.03 | 0.03 | 0.04 | 0.05 | 0.06 | | | | |
| Foil, bright | (h) | 0.06 | 0.07 | 0.07 | | | | | | | | |
| Molybdenum | | | | | | | | | | | | |
| Polished | (h) | | | | | 0.06 | 0.08 | 0.10 | 0.12 | 0.15 | 0.21 | 0.26 |
| Shot-blasted, rough | (h) | | | | | 0.25 | 0.28 | 0.31 | 0.35 | 0.42 | | |
| Stably oxidized | (h) | | | | | 0.80 | 0.82 | | | | | |
| Nickel | | | | | | | | | | | | |
| Polished | (h) | | | | | 0.09 | 0.11 | 0.14 | 0.17 | | | |
| Stably oxidized | (h) | | | | | 0.40 | 0.49 | 0.57 | | | | |
| Platinum | | | | | | | | | | | | |
| Polished | (h) | | | | | | 0.10 | 0.13 | 0.15 | 0.18 | | |
| Silver | | | | | | | | | | | | |
| Polished | (h) | | | 0.02 | 0.02 | 0.03 | 0.05 | 0.08 | | | | |
| Stainless steels | | | | | | | | | | | | |
| Typical, polished | (n) | | | 0.17 | 0.17 | 0.19 | 0.23 | 0.30 | | | | |
| Typical, cleaned | (n) | | | 0.22 | 0.22 | 0.24 | 0.28 | 0.35 | | | | |
| Typical, lightly oxidized | (n) | | | | | | 0.33 | 0.40 | | | | |
| Typical, highly oxidized | (n) | | | | | | 0.67 | 0.70 | 0.76 | | | |
| AISI 347, stably oxidized | (n) | | | | | 0.87 | 0.88 | 0.89 | 0.90 | | | |
| Tantalum | | | | | | | | | | | | |
| Polished | (h) | | | | | | | | 0.11 | 0.17 | 0.23 | 0.28 |
| Tungsten | | | | | | | | | | | | |
| Polished | (h) | | | | | | 0.10 | 0.10 | 0.13 | 0.18 | 0.25 | 0.29 |

TABLE A.11 Continued

Nonmetallic Substances^b

| Description/Composition | | Temperature (K) | Emissivity ϵ |
|-------------------------------|------------|--------------------|--------------------------|
| Aluminum oxide | <i>(n)</i> | 600 | 0.69 |
| | | 1000 | 0.55 |
| | | 1500 | 0.41 |
| Asphalt pavement | <i>(h)</i> | 300 | 0.85–0.93 |
| Building materials | | | |
| Asbestos sheet | <i>(h)</i> | 300 | 0.93–0.96 |
| Brick, red | <i>(h)</i> | 300 | 0.93–0.96 |
| Gypsum or plaster board | <i>(h)</i> | 300 | 0.90–0.92 |
| Wood | <i>(h)</i> | 300 | 0.82–0.92 |
| Cloth | <i>(h)</i> | 300 | 0.75–0.90 |
| Concrete | <i>(h)</i> | 300 | 0.88–0.93 |
| Glass, window | <i>(h)</i> | 300 | 0.90–0.95 |
| Ice | <i>(h)</i> | 273 | 0.95–0.98 |
| Paints | | | |
| Black (Parsons) | <i>(h)</i> | 300 | 0.98 |
| White, acrylic | <i>(h)</i> | 300 | 0.90 |
| White, zinc oxide | <i>(h)</i> | 300 | 0.92 |
| Paper, white | <i>(h)</i> | 300 | 0.92–0.97 |
| Pyrex | <i>(n)</i> | 300 | 0.82 |
| | | 600 | 0.80 |
| | | 1000 | 0.71 |
| | | 1200 | 0.62 |
| Pyroceram | <i>(n)</i> | 300 | 0.85 |
| | | 600 | 0.78 |
| | | 1000 | 0.69 |
| | | 1500 | 0.57 |
| Refractories (furnace liners) | | | |
| Alumina brick | <i>(n)</i> | 800 | 0.40 |
| | | 1000 | 0.33 |
| | | 1400 | 0.28 |
| | | 1600 | 0.33 |
| | | 1600 | 0.40 |
| Magnesia brick | <i>(n)</i> | 800 | 0.45 |
| | | 1000 | 0.36 |
| | | 1400 | 0.31 |
| | | 1600 | 0.40 |
| Kaolin insulating brick | <i>(n)</i> | 800 | 0.70 |
| | | 1200 | 0.57 |
| | | 1400 | 0.47 |
| | | 1600 | 0.53 |
| Sand | <i>(h)</i> | 300 | 0.90 |
| Silicon carbide | <i>(n)</i> | 600 | 0.87 |
| | | 1000 | 0.87 |
| | | 1500 | 0.85 |
| Skin | <i>(h)</i> | 300 | 0.95 |
| Snow | <i>(h)</i> | 273 | 0.82–0.90 |

TABLE A.11 Continued*Nonmetallic Substances^b*

| Description/Composition | | Temperature (K) | Emissivity ϵ |
|-------------------------|--------------|--------------------|--------------------------|
| Soil | (<i>h</i>) | 300 | 0.93–0.96 |
| Rocks | (<i>h</i>) | 300 | 0.88–0.95 |
| Teflon | (<i>h</i>) | 300 | 0.85 |
| | | 400 | 0.87 |
| | | 500 | 0.92 |
| Vegetation | (<i>h</i>) | 300 | 0.92–0.96 |
| Water | (<i>h</i>) | 300 | 0.96 |

^aData from Reference 1.^bData from References 1, 9, 28, and 29.**TABLE A.12** Solar Radiative Properties for Selected Materials^a

| Description/Composition | α_s | ϵ^b | α_s/ϵ | τ_s |
|-----------------------------|------------|--------------|---------------------|----------|
| Aluminum | | | | |
| Polished | 0.09 | 0.03 | 3.0 | |
| Anodized | 0.14 | 0.84 | 0.17 | |
| Quartz overcoated | 0.11 | 0.37 | 0.30 | |
| Foil | 0.15 | 0.05 | 3.0 | |
| Brick, red (Purdue) | 0.63 | 0.93 | 0.68 | |
| Concrete | 0.60 | 0.88 | 0.68 | |
| Galvanized sheet metal | | | | |
| Clean, new | 0.65 | 0.13 | 5.0 | |
| Oxidized, weathered | 0.80 | 0.28 | 2.9 | |
| Glass, 3.2-mm thickness | | | | |
| Float or tempered | | | | 0.79 |
| Low iron oxide type | | | | 0.88 |
| Metal, plated | | | | |
| Black sulfide | 0.92 | 0.10 | 9.2 | |
| Black cobalt oxide | 0.93 | 0.30 | 3.1 | |
| Black nickel oxide | 0.92 | 0.08 | 11 | |
| Black chrome | 0.87 | 0.09 | 9.7 | |
| Mylar, 0.13-mm thickness | | | | 0.87 |
| Paints | | | | |
| Black (Parsons) | 0.98 | 0.98 | 1.0 | |
| White, acrylic | 0.26 | 0.90 | 0.29 | |
| White, zinc oxide | 0.16 | 0.93 | 0.17 | |
| Plexiglas, 3.2-mm thickness | | | | 0.90 |
| Snow | | | | |
| Fine particles, fresh | 0.13 | 0.82 | 0.16 | |
| Ice granules | 0.33 | 0.89 | 0.37 | |
| Tedlar, 0.10-mm thickness | | | | 0.92 |
| Teflon, 0.13-mm thickness | | | | 0.92 |

^aBased on tables from Reference 29.^bThe emissivity values in this table correspond to a surface temperature of approximately 300 K.

References

1. Touloukian, Y. S., and C. Y. Ho, Eds., *Thermophysical Properties of Matter*, Vol. 1, *Thermal Conductivity of Metallic Solids*; Vol. 2, *Thermal Conductivity of Nonmetallic Solids*; Vol. 4, *Specific Heat of Metallic Solids*; Vol. 5, *Specific Heat of Nonmetallic Solids*; Vol. 7, *Thermal Radiative Properties of Metallic Solids*; Vol. 8, *Thermal Radiative Properties of Nonmetallic Solids*; Vol. 9, *Thermal Radiative Properties of Coatings*, Plenum Press, New York, 1972.
2. Touloukian, Y. S., and C. Y. Ho, Eds., *Thermophysical Properties of Selected Aerospace Materials*, Part I: Thermal Radiative Properties; Part II: Thermophysical Properties of Seven Materials. Thermophysical and Electronic Properties Information Analysis Center, CINDAS, Purdue University, West Lafayette, IN, 1976.
3. Ho, C. Y., R. W. Powell, and P. E. Liley, *J. Phys. Chem. Ref. Data*, **3**, Supplement 1, 1974.
4. Desai, P. D., T. K. Chu, R. H. Bogaard, M. W. Ackermann, and C. Y. Ho, Part I: Thermophysical Properties of Carbon Steels; Part II: Thermophysical Properties of Low Chromium Steels; Part III: Thermophysical Properties of Nickel Steels; Part IV: Thermophysical Properties of Stainless Steels. CINDAS Special Report, Purdue University, West Lafayette, IN, September 1976.
5. American Society for Metals, *Metals Handbook*, Vol. 1, *Properties and Selection of Metals*, 8th ed., ASM, Metals Park, OH, 1961.
6. Hultgren, R., P. D. Desai, D. T. Hawkins, M. Gleiser, K. K. Kelley, and D. D. Wagman, *Selected Values of the Thermodynamic Properties of the Elements*, American Society of Metals, Metals Park, OH, 1973.
7. Hultgren, R., P. D. Desai, D. T. Hawkins, M. Gleiser, and K. K. Kelley, *Selected Values of the Thermodynamic Properties of Binary Alloys*, American Society of Metals, Metals Park, OH, 1973.
8. American Society of Heating, Refrigerating and Air Conditioning Engineers, *ASHRAE Handbook of Fundamentals*, ASHRAE, New York, 1981.
9. Mallory, J. F., *Thermal Insulation*, Van Nostrand Reinhold, New York, 1969.
10. Hanley, E. J., D. P. DeWitt, and R. E. Taylor, "The Thermal Transport Properties at Normal and Elevated Temperature of Eight Representative Rocks," *Proceedings of the Seventh Symposium on Thermophysical Properties*, American Society of Mechanical Engineers, New York, 1977.
11. Sweat, V. E., "A Miniature Thermal Conductivity Probe for Foods," American Society of Mechanical Engineers, Paper 76-HT-60, August 1976.
12. Kothandaraman, C. P., and S. Subramanian, *Heat and Mass Transfer Data Book*, Halsted Press/Wiley, Hoboken, NJ, 1975.
13. Chapman, A. J., *Heat Transfer*, 4th ed., Macmillan, New York, 1984.
14. Vargaftik, N. B., *Tables of Thermophysical Properties of Liquids and Gases*, 2nd ed., Hemisphere Publishing, New York, 1975.
15. Eckert, E. R. G., and R. M. Drake, *Analysis of Heat and Mass Transfer*, McGraw-Hill, New York, 1972.
16. Vukalovich, M. P., A. I. Ivanov, L. R. Fokin, and A. T. Yakovelev, *Thermophysical Properties of Mercury*, State Committee on Standards, State Service for Standards and Handbook Data, Monograph Series No. 9, Izd. Standartov, Moscow, 1971.
17. Tillner-Roth, R., and H. D. Baehr, *J. Phys. Chem. Ref. Data*, **23**, 657, 1994.
18. Kamei, A., S. W. Beyerlein, and R. T. Jacobsen, *Int. J. Thermophys.*, **16**, 1155, 1995.
19. Lemmon, E. W., M. O. McLinden, and M. L. Huber, *NIST Standard Reference Database 23: Reference Fluid Thermodynamic and Transport Properties-REFPROP*, Version 7.0 National Institute of Standards and Technology, Standard Reference Data Program, Gaithersburg, 2002.
20. Bolz, R. E., and G. L. Tuve, Eds., *CRC Handbook of Tables for Applied Engineering Science*, 2nd ed., CRC Press, Boca Raton, FL, 1979.
21. Liley, P. E., private communication, School of Mechanical Engineering, Purdue University, West Lafayette, IN, May 1984.
22. Liley, P. E., Steam Tables in SI Units, private communication, School of Mechanical Engineering, Purdue University, West Lafayette, IN, March 1984.
23. *Liquid-Metals Handbook*, 2nd ed., The Atomic Energy Commission, Department of the Navy, Washington, DC, 1952.
24. Perry, J. H., Ed., *Chemical Engineer's Handbook*, 4th ed., McGraw-Hill, New York, 1963.
25. Geankoplis, C. J., *Mass Transport Phenomena*, Holt, Rinehart & Winston, New York, 1972.
26. Barrer, R. M., *Diffusion in and Through Solids*, Macmillan, New York, 1941.
27. Spalding, D. B., *Convective Mass Transfer*, McGraw-Hill, New York, 1963.
28. Gubareff, G. G., J. E. Janssen, and R. H. Torborg, *Thermal Radiation Properties Survey*, Minneapolis-Honeywell Regulator Company, Minneapolis, MN, 1960.
29. Kreith, F., and J. F. Kreider, *Principles of Solar Energy*, Hemisphere Publishing, New York, 1978.

